



MEMORANDUM

TO: Prospective Bidders

FROM: Becky Smyth, Purchasing Director

RE: Request for Bid - #046-20 Cab and Chassis with Service Body

DATE: November 9, 2020, 2020

Enclosed you will find the necessary information for preparing and submitting your bid for **Cab and Chassis with Dump Body** for the City of Rome Georgia.

The deadline for submitting your bid is **December 3, 2020 at 11:00 a.m.** All questions regarding this bid should be sent to Jackson Abercrombie via e-mail jabercrombie@romegeorgia.us by **5:00 p.m. on November 24, 2020**. All questions and answers will be posted on the City website www.romegeorgia.com. It is the responsibility of the vendor to visit the site often to insure receipt of any new information that may be posted.

If you have further questions, please do not hesitate to call my office at 706-236-4410.

Becky Smyth
Purchasing Director

601 Broad Street • PO Box 1433 • Rome, Georgia 30162-1433
phone: 706/236-4410 • fax: 706/236-4549

www.romegeorgia.us

INSTRUCTIONS FOR BIDDERS

I. Bids must be received by **December 3, 2020 at 11:00 a.m.**

II. Bids must be delivered to:

City of Rome – Purchasing Department
Attention: Becky Smyth
601 Broad Street
Rome, Georgia 30161

III. Bids must be sealed and marked:

“Bid #046-20 Cab and Chassis with Service Body

IV. Bids must be complete and include:

- A. Completed Bid Proposal Form
- B. Executed Bidder’s Declaration
- C. Executed Certificate of Non-Discrimination
- D. Executed Affidavit of Non-Collusion
- E. Prompt Payment Affidavit
- F. Request for Taxpayer I.D. Number
- G. Drug-Free Workplace Certification
- H. E-Verify Compliance Affidavit
- I. SAVE Compliance Affidavit

All bids submitted shall be subject to acceptance or rejection and the City of Rome specifically reserves the right to accept or reject any or all bids, to waive any technicalities and formalities in the bidding.

Bidder shall submit all required forms and information simultaneously with sealed bids, which forms and information become a part of the property of the City of Rome and will not be returned to bidders unless a written request to withdraw is received prior to **December 3, 2020 at 11:00 a.m.**

V. Payment:

When contracts are awarded, payment by the City of Rome will be the normal 30-day cycle. However, the City does make every effort to honor all discounts.

REQUIREMENTS FOR BIDDERS

These items apply to and become a part of the terms and conditions of the bidders bid. Any exceptions must be in writing.

Notice is hereby given that the City of Rome will receive sealed bids from interested parties until **December 3, 2020 at 11:00 a.m.** at its offices located at 601 Broad Street, Rome, Georgia 30161.

Any bids received thereafter will not be considered.

Bids will be publicly opened and read at the City of Rome Purchasing Department located at 601 Broad Street, Rome, Georgia 30161 on the day and at the hour specified.

The purchaser may consider as non-responsive, any bid in which there is an alteration of, or departure from the bid form hereto attached.

The bid will be awarded to the lowest reliable bidder complying with the conditions of the invitation for bid. The bidder to whom award is made will be notified at the earliest possible date. The purchaser reserves the right to reject the bid of a bidder who has previously failed to perform properly or complete on time, contracts of a similar nature, or the bid of a bidder who, in the sole opinion and discretion of the purchaser is not in a position to perform the contract, or whose name appears on the United States Comptroller General's list of ineligible contractors.

Bids may be withdrawn by written or faxed request, provided such withdrawals are received prior to bid opening date.

NOTE: Unless stated on the bid form the bid submitted will assume all specifications will be met. Please note on the bid form all exceptions.

SPECIFICATIONS
046-20 Cab and Chassis with Service Body

The purpose of this specification is to describe a new, current model International MV 607 SBA 4x2 or comparable Cab and Chassis with Service Body. The use of a brand name does not indicate a preference for that brand. It is intended to establish a level of quality, function and reliability. The vehicle should be delivered ready to operate.

Please note: The City requests Factory Options when possible.

DESCRIPTION	COMPLY
International Model MV607 SBA 4X2 with 197.00 Wheelbase, 86.00 CA, 84.00 Usable CA, and 49.00 Axle to Frame.	_____
<u>Engine Specifications</u>	
Cummins B6.7 260 - EPA 2017, 260HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed,	_____
RADIATOR Aluminum, 2-Row, Cross Flow, Over Under System, 717 SqIn Louvered, with 313 SqIn Charge Air Cooler, Includes In-Tank	_____
HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps	_____
RADIATOR HOSES Premium, Rubber	_____
FAN DRIVE Horton Drivemaster Direct Drive Type, Two Speed with Residual Torque Device for Disengaged Fan Speed	_____
AIR CLEANER with Service Protection Element	_____
ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	_____
BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines	_____
BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door	_____
EMISSION COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal located on Driver Door	_____
FEDERAL EMISSIONS Cummins B6.7 EPA, OBD and GHG Certified for Calendar Year 2020	_____
OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines	_____

THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic, Stationary Pre-Set, Two Speed Settings; Mounted on Steering Wheel _____

ENGINE EXHAUST BRAKE for Cummins ISB/B6.7 Engine with Variable Vane Turbo Charger _____

ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls, with Ignition Switch Control, for Cummins ISB/B6.7 _____

Transmission Specifications

TRANSMISSION, AUTOMATIC Allison 3500 RDS 5th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway _____

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter _____

NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released _____

PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring _____

TRANSMISSION FEATURE EFFECTS for Allison, Disable Aftertreatment Regeneration When in PTO Mode _____

TRANSMISSION OIL Synthetic _____

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter _____

TRANSMISSION DIPSTICK Relocated to Right Side of Transmission _____

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223 _____

SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming _____

PTO LOCATION Customer Intends to Install PTO at Left Side of Transmission _____

Front Axle and Suspension

AXLE, FRONT NON-DRIVING Meritor MFS-14-122A I-Beam Type, 14,000-lb Capacity

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers

SPRING PINS Rubber Bushings, Maintenance-Free

SPRINGS, FRONT AUXILIARY Rubber

WHEELS, FRONT {Accuride 51408} DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(2) TIRE, FRONT 11R22.5 Load Range G ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position

STEERING GEAR {Sheppard M100} Power

STEERING COLUMN Tilting

STEERING WHEEL 4-Spoke; 18" Dia., Black

Rear Axle and Suspensions

AXLE, REAR, SINGLE Meritor MS-21-14X-3DCL Single Reduction, 21,000-lb Capacity, Driver Controlled Locking Differential, 190 Wheel Ends . Gear Ratio: 4.88

SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

AXLE, REAR, LUBE EmGard FE-75W-90 Synthetic Oil; 30 thru 39.99 Pints

WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

(4) TIRE, REAR 11R22.5 Load Range G G622 RSD (GOODYEAR), 497 rev/mile, 75 MPH, Drive

DRIVELINE SYSTEM {Dana Spicer} Service Free SPL170

Cab Specifications

Conventional 6-Man Crew Cab

FRONT END Tilting, Fiberglass, with Three Piece Construction _____

GRILLE Chrome _____

MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension _____

CLEARANCE/MARKER LIGHTS (5) Flush Mounted _____

ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Crew Cab _____

AIR CONDITIONER with Integral Heater and Defroster _____

OVERHEAD CONSOLE Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger _____

DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted _____

SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap _____

CAB REAR SUSPENSION Air Suspension, for Mid Cab Height _____

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood _____

GAUGE CLUSTER Premium Level; English with English Speedometer and Tachometer, for Air Brake Chassis, Includes Engine Coolant, Temperature, Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 5 Inch LCD Color Display _____

VIRTUAL GA, OIL TEMP, AUTO XMSN for Allison Transmission, Requires Premium Cluster _____

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster _____

COVER PLATE Blank Steel Cover Plate in Place of Storage Bin for Customer Back Up Camera Mounting Requirements _____

INSTRUMENT PANEL Flat Panel _____

MIRRORS (2) C-Loop, Power Adjust, Heated, LED Clearance Lights, Bright Heads and Arms, 7" x 14.5", Includes 8" x 6" Convex Mirrors, for 96" Load Width _____

SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust

SEAT, REAR {National} BENCH; Full Width; Vinyl, with Fixed Back and Two Integral Outboard Headrests

SEAT, TWO-MAN PASSENGER {National} Fixed Back, Integrated Headrest in Both Occupant Positions, Vinyl, Less Under Seat Storage Compartment

WINDOW, POWER (4) And Power Door Locks, Front and Rear Doors, Left and Right, Includes Express Down Feature

KEYLESS ENTRY system remote with Panic Alarm and Horn Beep Lock Confirmation, with Auxiliary Button for Work Light Function Includes One Key Fob

GRAB HANDLE, ADDITIONAL EXT (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, Mounted Left and Right Side, Rear of Rear Doors, for Crew Cab

Frame Specifications

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm)

BUMPER, FRONT Contoured, Steel, Chrome Plated

PTO EFFECTS, FRAME {Navistar} Lower Flange Trim for PTO Clearance

TOW HOOK, FRONT (2) Frame Mounted

Brake Specifications

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

BRAKE LINES Color and Size Coded Nylon

DRAIN VALVE Twist-Type

GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster

PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel

QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4

SLACK ADJUSTERS, FRONT Automatic (with Air Cam Brakes) _____

SLACK ADJUSTERS, REAR Automatic (with Air Cam Brakes) _____

SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6 _____

AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System _____

BRAKES, FRONT, AIR CAM S-Cam; 16.5" x 5.0"; Includes 20 Sq. In. Long Stroke Brake Chambers _____

BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn _____

BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake _____

BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake _____

AIR COMPRESSOR {Cummins} 18.7 CFM _____

AIR DRYER {Bendix AD-IP} with Heater _____

AIR DRYER LOCATION Mounted Outside Right Rail, Forward of Front Wheel _____

AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail _____

DRAIN VALVE {Berg} with Pull Chain, for Air Tank _____

Exhaust Systems

EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab, for Single Long Horizontal Tail Pipe _____

TAIL PIPE (1) Horizontal, Long, Exits Right Side Outside of Body at Rear Wheels _____

AFTERTREATMENT COVER Steel, Black _____

SWITCH, FOR EXHAUST 2 Position, Lighted & Latching, On/Off Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as Long as Switch is in On Position _____

Electrical Systems

ELECTRICAL SYSTEM 12-Volt, Standard Equipment _____

DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab	_____
HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel	_____
HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever	_____
PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light	_____
STARTER SWITCH Electric, Key Operated	_____
STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector	_____
TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature	_____
TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted	_____
WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever	_____
WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted	_____
WIRING, CHASSIS Color Coded and Continuously Numbered	_____
ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount, with Remote Sense	_____
BATTERY BOX Steel, with Plastic Cover, 25" Wide, 2-3 Battery Capacity, Mounted Left Side Back of Cab	_____
BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud	_____
BATTERY DISCONNECT SWITCH {Cole-Hersee 75920-06} 300 Amp, Disconnects Charging Circuits, Locks with Padlock, Battery Box Mounted	_____
BODY BUILDER WIRING Back of Day Cab Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	_____
CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	_____

CIGAR LIGHTER Includes Ash Cup _____

HEADLIGHTS Halogen, Composite Aero Design, with Daytime Running Lights _____

HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord _____

HORN, ELECTRIC Disc Style _____

INDICATOR, LOW COOLANT LEVEL with Audible Alarm _____

POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) & USB Port, Located in the Instrument Panel _____

RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input, MP3, Apple Device Play & Control _____

SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars _____

STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt, Less Thermal Over-Crank Protection _____

TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights _____

ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket _____

SWITCH, BODY CIRCUITS, MID with Remote Power Module Mounted on Battery Box Back of Cab, Up to 6 Outputs & 6 Inputs Each, Max 20 amp per Channel, Max 80 amp Total, Includes 1 Switch Pack with Momentary Switches _____

IGNITION SWITCH Keyless _____

INDICATOR, BATTERY WARNING Green BATTERY ON Indicator, Mounted on Left Side of Instrument Panel, To be Used with Factory Installed or Customer Mounted Battery Disconnect Switch _____

POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) & USB Port, Located in the Instrument Panel _____

POWER SOURCE Cigar Type Receptacle without Plug and Cord _____

JUMP START STUD Remote Mounted

TRAILER CONNECTION SOCKET {Phillips} 7-Way, Mounted at Rear of Frame, Wired for Turn Signals Combined with Stop, Compatible with Trailers with Combined Stop, Tail, Turn Lamps

Fuel Tanks

FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab

DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab

FUEL/WATER SEPARATOR 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor, Cummins Supplied on Engine

Services Section:

Fuel, wash, DOT, DOT KIT

Move / Install exterior Grab Handles lower position on B and C Pillars

Front and Rear Aluminum Wheel Simulators

Back Up Camera - in dash monitor with 15 feet additional line bundled to rear of frame, camera shipped loose for up fitter installation

Transport from Body Company

Warranty

BASIC VEHICLE COVERAGE

Basic Vehicle Warranty 24 months / Unlimited miles

Chassis Coverage

Frame side rails 84 months unlimited miles

Cab/cowl structure 60 months unlimited miles

Cab/cowl perforation corrosion 60 months unlimited miles

Vendor Drivetrain Coverage

Cummins Engine, B6.7 Engine, 36 months unlimited miles

Allison Transmission, 36 months unlimited miles

Meritor Axles, 36 months unlimited miles

Base Warranty Exceptions

Batteries 12 months unlimited miles _____

Brightwork, Chassis Paint and Corrosion (other than Cab) 6 months unlimited miles _____

Hood/Cab Paint 12 months unlimited miles _____

Towing - First 90 days for Vehicle Down Situations Only - limited _____

Service Body Specifications

11 foot Reading PB63-HD132A _____

White powder coated body _____

Master Lock cabinets and side door _____

Keyless electric lock FOB unlocks cab doors, all side cabinets, and side door
Locate electrical lock wiring block in shielded cover above side door header
by hinges (do not affix with rivets that would put holes in exterior sheet
metal) _____

Textured coating in all cabinet interior walls and top _____

Hidden hinges all cabinet doors. _____

DRIVER SIDE (Street Side) Four (4) Cabinets

1 horizontal above wheel well _____

3 vertical _____

Shelves with 2" spaced diver slots _____

Two in horizontal cabinet _____

Three each vertical cabinet _____

Twenty dividers for horizontal cabinet _____

Wheel chock storage pockets on front and rear of wheel well. _____

PASSENGER SIDE (Curb Side) Three cabinets and swing out door

Cabinets:

1 horizontal above wheel well

1 vertical cabinet

1 slim vertical cabinet

Shelves with 2" spaced dividers slots:

Two in horizontal cabinet

Three in slim vertical cabinet

Twenty dividers for horizontal cabinet

Wheel chock storage pockets on front and rear of wheel well

Drawer set curbside rear cabinet:

three (3) 6" tall drawers

two (2) 8" tall drawer

Installed to approx. 11" from cabinet top

Thor 3000 watt inverter

Install above drawer set.

Side door

Swing type

Window approx. 18" square

Two step stepwell diamond plate

Antiskid runner

Handrail on bulkhead

Additional exterior access step under side door entry same height and
Appearance of crew cab access step.

Canopy and Interior Specifications

Interior height 64" Floor to roof

Exterior horizontal ribs for added strength

Three shelves 17" deep with front lip

Bottom of shelves from floor @ 28.5, 40.5, 52.5 inches each side

12" deep shelf with front lip located 12 inches from top of canopy rear wall

Metal hooks swivel type (foldable)

2 on street side evenly spaced

1 on curb side

2 on front wall

Sign storage partition at bulkhead - two pieces of flat bar mounted 2 inches from bulkhead 38 inches from floor spaced 15" o/c. Rhino Line or equal lining on floor and 28.5" from floor on interior bins.

Rear of Body Specifications

Shutter door 45" min height opening width matches interior distance of cabinet separation

Electric receptacle two plug GFI weatherproof plate at Rear of Body passenger side rear connected to power inverter

Heavy duty rear boxed bumper 8" x 10" antiskid surface

Heavy duty G I pintle hitch and safety chain D rings

Seven way plug trailer connector plug.

Strobes and Directional Bars

Strobe lights clear lens amber flash - 2 front of body, 2 rear of body, 2 front grille of truck

Front of body trim line directional bar

Rear od body directional light - dominator 8 led lighting with tad series control head

Three position lighted switch (one flash mode, one direct left, one direct right) for directional bars and strobes

Canopy and cabinet Lights

C2 lighting package lighting in all cabinets and under shelves in bins

Four (4) interior LED lamps evenly spaced in canopy interior above cabinets for best shelving visibility

Lighted switch in dash controls on / off for canopy and cabinet shelf lights.

Flood Lights

DRIVER SIDE (street side) flood lights

Two (2) recessed exterior mount side spot lights

45 degree angle with ability to adjust vertically

Projected work distance 22ft from side

Located near front and rear of canopy

Lighted switch in dash controls on / off for driver side flood lights.

Passenger Side (Curbside) Flood Lights

Two (2) recessed exterior mount side spot lights

45 degree angle with ability to adjust vertically

Projected work distance 22ft from side

Locate near rear of body and above trailing edge of side door

Lighted switch in dash controls on / off for curbside side flood lights.

Rear of Body

Exterior surface mounted spot lamp (for illumination of bumper and trailer connection and trailer)

Located below direction bar

Lighted switch in dash controls on / off for rear flood light.

Compressed Air System

Remote engine start / stop / PTO engagement (requires chassis manufactures'' provision for remote start / stop / PTO engagement) _____

Vanair underdeck system _____

UDSM 185 cfm / 100 psig mount under passenger side rear door _____

Hose reel location under the step curbside rear door steps _____

3/4 hose 100 ft. _____

Electrical

Battery isolator to Prevent over draw of battery power _____

Connect chassis supplied back up camera to top center top of canopy. _____

BID FORM

TO: City of Rome – Purchasing Department
ATTN: BECKY SMYTH
601 Broad Street
Rome, Georgia 30161

BID PKG. "046-20 Cab and Chassis with Service Body"

Quantity	Description	Total
1	Cab and Chassis with Service Body	_____

Cab and Chassis Proposed: _____

Service Body Proposed: _____

Expected Delivery Date: _____

FOB-Delivered: 100 Vaughn Rd., Rome Georgia 30161

All bids submitted shall be subject to acceptance or rejection and the City of Rome specifically reserves the right to accept or reject any or all bids, to waive any technicalities and formalities in the bidding.

The undersigned understands that any conditions stated above, clarifications made to the above or information other than that requested should be under separate cover and to be considered only at the discretion of the Purchasing Department.

Name of Individual, Partner
or Corporation

Company

Title

Address

Authorized Signature

City, State, Zip Code

Company Phone Number _____

Please attach contact's business card:

BIDDERS DECLARATION

The bidder understands, agrees and warrants:

- That the bidder has carefully read and fully understands the full scope of the specifications.
- That the bidder has the capability to successfully undertake and complete the responsibilities and obligations in said specifications.
- That the bidder has liability insurance and a declaration of insurance form is included in the bid package.
- That this bid may be withdrawn by requesting such withdrawal in writing at any time prior to **December 3, 2020 at 11:00 a.m.** but may not be withdrawn after such date and time.
- That the City of Rome reserves the right to reject any or all bids and to accept that bid which will, in its opinion, best serve the public interest. The City of Rome reserves the right to waive any technicalities and formalities in the bidding.

- That by submission of this bid the bidder acknowledges that the City of Rome has the right to make any inquiry or investigation it deems appropriate to substantiate or supplement information supplied by the bidder.

If a partnership, a general partner must sign.

If a corporation, the authorized corporate officer(s) must sign and the corporate seal must be affixed to this bid.

BIDDER:

Name

Title

Name

Title

AFFIX CORPORATE SEAL (If Applicable)

CERTIFICATE OF NON-DISCRIMINATION

In connection with the performance of work under this contract, the bidder agrees as follows:

The bidder agrees not to discriminate against any employee or applicant for employment because of race, creed, color, sex, national origin, ancestry or disability. The vendor shall take affirmative action to insure that employees are treated without regard to their race, creed, color, sex, national origin, ancestry or disability. Such action shall include, but not be limited to the following: employment, upgrading, demotion, transfer, recruiting or recruitment, advertising, lay-off or termination, rates of pay or other compensation and selection for training, including apprenticeship.

In the event of the bidder's non-compliance with this non-discrimination clause, the contract may be canceled or terminated by the City of Rome. The bidders may be declared, by the City of Rome, ineligible for further contracts with the City of Rome until satisfactory proof of intent to comply shall be made by the vendor.

The bidder agrees to include this non-discrimination clause in any sub-contracts connected with the performance of this agreement.

BIDDER

SIGNATURE

TITLE

NON-COLLUSION AFFIDAVIT

The following affidavit is to accompany the bid:

STATE OF

COUNTY OF

Owner, Partner or Officer of Firm

Company Name, Address, City and State

Being of lawful age, being first duly sworn, on oath says that he/she is the agent authorized by the bidder to submit the attached bid. Affidavit further states as bidder, that they have not been a party to any collusion among bidders in restraint of competition by agreement to bid at a fixed price or to refrain from bidding; or with any office of the City of Rome or any of their employees as to quantity, quality or price in the prospective contract; or any discussion between bidders and any official of the City of Rome or any of their employees concerning exchange of money or other things of value for special consideration in submitting a sealed bid for:

FIRM NAME _____

SIGNATURE _____

TITLE _____

Subscribed and sworn to before me this _____ day of 20____

NOTARY PUBLIC

CITY OF ROME

DRUG-FREE WORKPLACE CERTIFICATE

By signature on this certificate, the Bidder certifies that the provisions of O.C.G.A. Section 50-24-1 through 50-24-6 related to the "Drug-Free Workplace Act" will be complied with in full. The Bidder further certifies that:

1. A drug-free workplace will be provided for the Bidder's employees during the performance of the contract; and
2. Each contractor who hires a subcontractor to work in a drug-free workplace shall secure from that subcontractor the following written certification: "As part of the subcontracting agreement with (contractor's name), (subcontractor's name) certifies to the contractor that a drug-free workplace will be provided for the subcontractor's employees during the performance of this contract pursuant to O.C.G.A. Section 50-24-3(b)(7)."

By signature on this certificate, the Bidder further certifies that it will not engage in the unlawful manufacture, sale, distribution, dispensation, possession, or use of a controlled substance or marijuana during the performance of the contract.

Bidder: _____

By: _____

Name Printed: _____

Title: _____

Date: _____

CITY OF ROME, GEORGIA
SAVE COMPLIANCE AFFADAVIT
O.C.G.A § 50-36-1(e) (2) Affidavit

By executing this affidavit under oath, as an applicant for a (n) Contract or Services, as referenced O.C.G.A. C. § 50-36-1, from the City of Rome, Georgia, the undersigned applicant verifies one of the following with respect to my application for a public benefit:

- 1) _____ I am a United State citizen.

- 2) _____ I am a legal permanent resident of the United States

- 3) _____ I am a qualified alien or non-immigrant under the Federal Immigration and Nationality Act with an alien number issued by the Department of Homeland Security or other federal immigration agency.
My alien number issued by the Department of Homeland Security or other federal immigration agency is: _____.

The undersigned applicant also hereby verifies that he or she is 18 years of age or older and has provided at least one secure and verifiable document, as required by O.C.G.A. § 50-36-1(e)(1), with this affidavit.

The secure and verifiable document provided with this affidavit can best be classified as: _____.

In making the above representation under oath, I understand that any person who knowingly and willfully makes a false, fictitious, or fraudulent statement or representation in an affidavit shall be guilty of a violation of O.C.G.A. § 16-10-20, and face criminal penalties as allowed by such criminal statute.

Executed in _____ (city), _____ (state).

Signature of Applicant

Printed Name of Applicant

SUBSCRIBED AND SWORN
BEFORE ME ON THIS THE
_____ DAY OF _____, 20____

NOTARY PUBLIC
CITY OF ROME, GEORGIA

E-VERIFY COMPLIANCE AFFADAVIT

By executing this affidavit, the undersigned contractor verifies its compliance with O.C.G.A. § 13-10-91, stating affirmatively that the individual, firm or corporation which is engaged in the physical performance of services on behalf of the City of Rome, Georgia has registered with, is authorized to use and uses the federal work authorization program commonly known as E-Verify, or any subsequent replacement program, in accordance with the applicable provisions and deadlines established in O.C.G.A. § 13-10-91. Furthermore, the undersigned contractor will continue to use the federal work authorization program throughout the contract period and the undersigned contractor will contract for the physical performance of services in satisfaction of such contract only with subcontractors who present an affidavit to the contractor with the information required by O.C.G.A, § 13-10-91 (b). Contractor hereby attests that its federal work authorization user identification number and date of authorization are as follows:

Federal Work Authorization User Identification number
(Not Required if Less than 10 Employees)

Signature (if less than 10 employees)

Date of Authorization

Name of Contractor/Company

Name of Project

Name of Public Employer

I hereby declare under penalty of perjury that the foregoing is true and correct.

Executed on _____, _____, 20____ in _____ (city) _____ (state).

Signature of Authorized Officer or Agent

Printed Name and Title of Authorized Officer or Agent

SUBSCRIBED AND SWORN BEFORE ME
ON THIS THE _____ DAY OF _____, 20____

NOTARY PUBLIC
My Commission Expires:
Commission Expires: